

# Baldor Premier Generators

**Baldor Premier Series**, the name says it all. Premier's performance and durability have made it the "generator of choice" in the rental and construction industry. Baldor manufactures the Premier Series to the most stringent specifications to ensure that you'll get the highest quality brushless two pole generator on the market. Add to this the quality of an ISO 9001 certified manufacturing plant and a 3 year product warranty and you'll see why the Premier Series has truly earned its name.



R30



OHV30



R60



OHV110E

## Premier Features

### Switchless Full Pow'R

*All the POWER, All the TIME!®*

- Premier generators with "Switchless Full Pow'R" do not need a "power switch." We're always full power!
- Plug in 120v or 240v in any combination.
- No need to change voltage settings.
- No need to worry about which cord is plugged in.
- No complicated formulas and instructions.
- Reduces the chance for generator damage.

### Automatic Idler

- Automatically idles engine when load is removed.
- Reduces fuel consumption.
- Reduces engine noise.
- Extends engine life.

### 3-Year Warranty

### Focal Vibration System

### Optional Dolly Kits

**Models:** R30, OHV30, OHV40, R45, R45E, R60, R60E, OHV50H, OHV60, OHV60E, OHV85E, OHV100E, OHV110E

**BALDOR**  
**GENERATORS**

# REAL RELIABLE POWER W

## R30 - 3000 Watts

- Robin/Subaru industrial grade engine
- GFCI receptacles
- Low oil shutdown
- Automatic Idler
- Fully enclosed tube frame
- 3-year commercial warranty



## OHV30 - 3000 Watts

- Honda commercial grade OHV engine
- AC circuit breakers
- Large fuel tank
- GFCI receptacles
- 3-year commercial warranty



## R45/R45E - 4500 Watts

## R60/R60E - 6000 Watts

- Robin/Subaru industrial grade engine
- Switchless Full Pow'R
- Automatic Idler
- AC Voltmeter
- Focal Vibration System
- 3-year commercial warranty
- Recoil or Electric Start



## OHV40 - 4000 Watts\*

## OHV50H - 5000 Watts

## OHV60/OHV60E - 6000 Watts

- Honda commercial grade OHV engine
- Switchless Full Pow'R
- GFCI receptacles
- Focal Vibration System
- AC Voltmeter
- Automatic Idler
- 3-year commercial warranty
- Recoil or Electric Start

\* OHV40 – Recoil only



# WITH BALDOR GENERATORS

## OHV85E - 9000 Watts OHV100E - 10,500 Watts

- Vanguard industrial grade engine
- *Switchless Full Pow'R*
- Electric start with recoil
- *Automatic Idler*
- 3-year commercial warranty



## OHV110E - 11,000 Watts

- Honda commercial grade OHV engine
- *Switchless Full Pow'R*
- Electric start
- *Automatic Idler*
- 3-year commercial warranty



## Focal Vibration System

- Virtually eliminates harmful vibration
- Less vibration = longer generator life
- Neoprene isolators = more durable than rubber.



## Optional Dolly Kits

**Two Wheel Kit** – Includes 10" pneumatic wheels, fold down handles, power cable storage hanger, axle and mounting hardware.

**Four Wheel Kit** – 10" pneumatic wheels, axles and mounting hardware.



GFCI receptacles, voltmeter, AC circuit breakers, hourmeter.

OHV110E Panel is displayed to show a variety of features. Panels may vary by model.

Premier Model		R30	R45 or R45E	R60 or R60E	OHV30	OHV40	OHV50H	OHV60 or OHV60E	OHV110E	OHV85E	OHV100E
<b>GENERAL FEATURES</b>	Switchless Full Pow'R		•	•		•	•	•	•	•	•
	AC Voltmeter		•	•		•	•	•	•	•	•
	Hourmeter	•	•	•	•	•	•	•	•	•	•
	AC Circuit Breakers	•	•	•	•	•	•	•	•	•	•
	Low Oil Shutdown	•	•	•	•	•	•	•	•	•	•
	Automatic Idler	•	•	•		•	•	•		•	•
	Voltage Regulation								•		•
	Spark Arrestor Muffler	•	•	•	•	•	•	•		•	•
	Extended Run Fuel Tanks	•	•	•	•	•	•	•	•	•	•
	Tubular Roll Cage	•	•	•	•	•	•	•	•	•	•
	Neoprene Isolators	•	•	•	•	•	•	•	•	•	•
	Focal Vibration System (FVS)		•	•		•	•	•	•	•	•
	*3 Year Commercial Warranty	•	•	•	•	•	•	•	•	•	•
<b>SPECIFICATIONS</b>	<b>Engine</b>	<b>Robin/ Subaru</b>	<b>Robin/ Subaru</b>	<b>Robin/ Subaru</b>	<b>Honda</b>	<b>Honda</b>	<b>Honda</b>	<b>Honda</b>	<b>Honda</b>	<b>Vanguard</b>	<b>Vanguard</b>
	<b>Model</b>	<b>EH17</b>	<b>EH25</b>	<b>EH34</b>	<b>GX160</b>	<b>GX240</b>	<b>X270</b>	<b>GX340</b>	<b>GX620</b>	<b>303477</b>	<b>350477</b>
	Horsepower	5.5 Hp	8.0 Hp	11.0 Hp	5.5 Hp	8.0 Hp	9.0 Hp	11.0 Hp	20.0Hp	16.0 Hp	18.0 Hp
	Cylinder(s)	1	1	1	1	1	1	1	2	2	2
	Displacement – cc	172	231	338	163	242	270	337	614	480	570
	Lubrication System	Splash	Splash	Splash	Splash	Splash	Splash	Splash	Pressure	Pressure	Pressure
	Starting Systems (Battery not included on Electric Start models)	Recoil	Recoil or 12 Volt with Recoil	Recoil or 12 Volt with Recoil	Recoil	Recoil	Recoil	Recoil or 12 Volt with Recoil	12 Volt Electric	12 Volt with Recoil	12 Volt with Recoil
	<b>Rating</b>	3000W Max.	4500W Max.	6000W Max.	3000W Max.	4000W Max.	5000W Max.	6000W Max.	11,000W Max.	9000W Max.	10,500W Max.
		2500W Rated	4000W Rated	5000W Rated	2500W Rated	3500W Rated	4000W Rated	5000W Rated	10,000W Rated	8000W Rated	9,500W Rated
		120V AC	120/240V AC	120/240V AC	120V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC
		20.8A	33.3/16.7A	41.6/20.8A	20.8A	29.2/14.6	33.3/16.7A	41.6/20.8A	83.3/41.6A	66.7/33.4A	79.2/39.6A
	<b>Sound Ratings</b> db(A) at 23 feet (7 meters)	66.9	70.9	72.8	69.9	73.0	73.0	72.4	78.0	75.4	75.3
	<b>Receptacles</b>										
	Straight (5-20R GFCI) 120V	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp
	Twist Lock (L530R) 120V		1-30 Amp	1-30 Amp		1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp
	Twist Lock (L1430R) 120/240V		1-30 Amp	1-30 Amp		1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp
	Twist Lock (CS6369) 120/240V								1-50 Amp		1-50 Amp
Fuel Capacity (U.S. gallons)	3.2	4.4	4.4	2.8	4.6	4.6	4.6	5.8	5.8	5.8	
Operational Run Time /1 tankful	6-9 hours	5-9 hours	4.5-8 hours	5-8 hours	6-10 hours	6-10 hours	4-7 hours	4-6 hours	4-7 hours	4-6 hours	
<b>Dimensions</b>											
Length	22 1/2"	27"	27"	25 1/2"	28"	28"	28"	30"	28"	30"	
Width	15 3/4"	18 1/4"	18 1/4"	17 1/2"	20 1/2"	20 1/2"	20 1/2"	23"	21 1/2"	23"	
Height	20 1/2"	23 1/4"	23 1/4"	18"	22 1/4"	22 1/4"	22 1/4"	28 1/2"	27 1/2"	28 1/2"	
		(20 1/4"W- R45E)	(20 1/4"W- R60E)								
<b>Weight</b>											
Net Dry	110 lbs.	170 lbs./ 175 lbs.	195 lbs./ 200 lbs.	112 lbs.	170 lbs.	170 lbs.	192 lbs./ 206 lbs.	270 lbs.	224 lbs.	270 lbs.	

**WARNING:** Do not connect generator to any building's electrical system unless a disconnect switch has been installed.

**NOTES:** • Due to our continuing effort for product improvement, specifications subject to change without notice.  
\* Engine warranty per manufacturer.

**BALDOR**  
**GENERATORS**

3815 Oregon Street • Oshkosh, WI 54902  
1-800-872-7697 • (920) 236-4200 • Fax (920) 236-4219



World Headquarters

Baldor Electric Company • P.O. Box 2400 • Fort Smith, AR 72902-2400 U.S.A.  
Phone (479) 646-4711 • Fax (479) 648-5792 • International Fax (479) 648-5895

www.baldor.com